

## Technical Information

<b>Product</b>	
<b>Input device</b>	<b>1x powerCON® TRUE1® TOP</b>
<b>Output device</b>	<b>7x powerCON® TRUE1® TOP</b>
<b>Daisy chaining</b>	<b>1x powerCON® TRUE1® TOP</b>
<b>Electrical</b>	
<b>Contact resistance / protection class</b>	<b>Protection class II</b>
<b>Dielectric strength</b>	<b>0.5 kV / mm</b>
<b>Rated voltage</b>	<b>120V AC</b>
<b>Rated Current</b>	<b>20A</b>
<b>Number of electrical contacts</b>	<b>2 + PE</b>
<b>Phases</b>	<b>single-phase</b>
<b>Mechanical</b>	
<b>Lifetime</b>	<b>&gt; 5000 Mating cycles</b>
<b>Dimensions</b>	<b>220 x 150 x 65 mm</b>
<b>Conductor cross section</b>	<b>AWG12</b>
<b>Weight</b>	<b>1.0 kg</b>

<b>Mounting options</b>	<b>Truss clamp, mounting wholes for pegging or suspension</b>
<b>Type of construction</b>	<b>Stackable</b>
<b>Material</b>	
<b>Housing</b>	<b>Easylen</b>
<b>Color</b>	<b>black</b>
<b>Environmental</b>	
<b>Standards compatibility</b>	<b>UL94-V0</b>
<b>Protection class</b>	<b>NEMA1 listed. IP20.</b>
<b>Temperature range</b>	<b>-25 °C to +70 °C</b>
<b>Compliance</b>	
<b>Standard Compliance</b>	<b>ETL Listed. Compliant to UL STD 1640</b>